

Details:


- LinearLight 3-TW7.3 is a medium profile, versatile, tunable white LED strip with best-in-class CRI available for a variety of applications. LinearLight 3-TW7.3 is provided in an output of 517lm/ft.
- Stocked in 192" lengths but can be factory cut and delivered to project site based on site specific measurements by the Convey Team.

Physical Features:


- Factory cut lengths to 1.64" Increments.
- 3M (300LSE) yellow adhesive tape attached on backside, standard
- Complete factory assembly with any Series BE3 Profiles.
- 96" Power Leads

Lighting Features:

- 120° beam spread
- 50,000hr. Life (L70)
- 5 year warranty
- TM-30 data available at www.conveylighting.com



Profile:



Specifications:

Average Power Consumption	7.3W/ft.
Voltage	24V/dc
Binning	3 step
Cut Increment	1.64"
Diodes per foot	175
Max. Run	13ft.
IP Rating	IP20 (Class II dry location)
Dimensions	0.48"W x 0.04"H

CCT	Lumen Output (lm/ft.)	Efficacy (lm/W)
2700K, 6500K @98CRI	517	71
1800K@90CRI, 4000K @98CRI	517	71
1800K@90CRI, 3000K @98CRI	517	71

Ordering Information:

Example:
L3-TW7.3-27/65-30'

Model:	CCT:	Length:	Transformer/PSU
L3-TW7.3 7.3W/ft.	27/65 2700K/6500K 18/40 1800K/4000K 18/30 1800K/3000K	1'-16' C SPECIFY CUSTOM	TXXX SPECIFIED SEPARATELY



LM-80

